

SPIRAL-LITE™ Covered

Compact Fluorescent Lamps



G25

R30

R40

PAR38

A19

Features and Benefits

- 8,000 to 10,000-hour life
- Energy Star qualified
- Up to 80% energy savings compared to incandescent
- Same familiar shapes as incandescent
- Fits standard fixtures
- 1-year warranty

Applications

- General lighting
- Table lamps
- Floor lamps
- Ceiling fixtures
- Recessed cans
- Track lighting
- Theatres
- Bathrooms
- Vanities

Spiral-Lite Covered CFLs Offer Attractive Savings in Familiar Shapes

Litetronics Spiral-Lite™ Covered CFLs come in a variety of familiar shapes to combine the energy savings of compact fluorescent lamps with the attractive look and feel of an incandescent. Available in A19, G25, R30, R40, and PAR38, Spiral-Lite Covered CFLs provide up to 80% energy savings in a wide range of applications. These energy savings help lower utility bills and reduce greenhouse gas emissions.

Spiral-Lite Covered CFLs are Energy Star qualified and have an average life of 8,000 to 10,000 hours. This helps reduce replacement, labor, and maintenance costs. In addition to their familiar shapes, Spiral-Lite Covered CFLs have a 2700K color temperature that provides the same warm lighting as incandescent lamps. Replace inefficient incandescent lamps while maintaining the same attractive look with Spiral-Lite Covered CFLs.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

SPIRAL-LITE™ Compact Fluorescent Lamps

Covered



A19



G25



R30



PAR38



R40

LAMP	WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	QTY/ CASE	AVERAGE RATED LIFE	CRI	CORRELATED COLOR TEMP(K)	INITIAL LUMENS	MEAN LUMENS	M.O.L.**
A19	9 \$	MED	120	9W A19 27	L-9527A19	50	10,000	82	2700	535	475	4.29"
	14 \$	MED	120	14W A19 27	L-14527A19	50	8,000	82	2700	825	725	4.88"
G25	11 \$	MED	120	11W G25 27	L-11527G25	24	8,000	82	2700	550	550	4.33"
	14 \$	MED	120	14W G25 27	L-14527G25	24	8,000	82	2700	900	825	4.33"
R30	15 \$	MED	120	15W R30 27	L-15527R30	50	8,000	82	2700	750	675	5.47"
R40	23 \$	MED	120	23W R40 27	L-23527R40	24	8,000	82	2700	1,300	1,175	6.34"
PAR38	23 \$	MED	120	23W PAR38 27	L-23527P38	24	8,000	82	2700	1,300	1,175	6.34"

SPECIFICATIONS

INPUT LINE FREQUENCY	50/60 HZ
RELIABLE OPERATING TEMP.	-5°F – 105°F
POWER FACTOR	> .50

CONVERSION CHART

CFL	=	INCANDESCENT
9-watt	=	40-watt
11-watt	=	40-watt
14-watt	=	60-watt
15-watt	=	65-watt
23-watt	=	120-watt

Energy Star Qualified

\$ Energy Savings

** Maximum Overall Length (in inches)

